



JUPITER PETROTEC PRODUCTS

[Mfrs of Automotive , Industrial , Speciality Products, Greases & Lube Additives]

Mktg & Admin Office : 18/27, Velu Street, West Mambalam, Chennai-600033

Factory: DP - 109 A, Sidco Industrial Estate, Kakkalur, Thiruvallur District-602003

Email: jupitolubricants@yahoo.co.in / jupitolubricants@gmail.com Website : www.jupitolubricants.com

Phone: 044-24892258 / 24718885 Mobile No. +91 98407 31961 / +91 6374709530

PRODUCT DATA SHEET

JUPITOL MP 3 GREASE

Product Category	Industrial Grease
Serial No	02
Date	01.04.2021

Product Description:

Jupitol Multi-purpose MP 3 Grease is lithium based multifunctional, high temperature, high shear stable and water resistant grease. It is premium quality multi-purpose grease having good thermal and structural stability with high drop point (melting point) and high oxidation resistance. It has provide excellent protection against rusting and corrosion on its lubricating surfaces.

Applications:

- In plain and anti-friction bearings, chassis fittings, grease cups and grease lubricated type universal joints.
- Recommended for all grease-lubricated parts of automobiles including commercial vehicles.
- Recommended for all the greasing applications of agricultural, industrial and construction machinery and equipments

Features:

- High drop point with good thermal and structural stability
- High degree of protection against rusting and corrosion with enhanced resistance to oxidation

Specification Level:

- Conforms to IS 7623 / 1993 (Industrial – Regular)

Typical Characteristics:

S.No.	Test	Test Method	Specification of Jupitol MP- 3 Grease
1	Colour	Visual	Light yellowish
2	Structure	Visual	Buttery
3	Soap Type	ASTM D	Lithium
4	Consistency of the Grease as per Worked Penetration @ 25°C	ASTM D 217	230 to 250 (NLGI-3)
5	Drop Point in °C	ASTM D 566	185
6	Base Oil Kin. Viscosity @ 100°C	ASTM D 445	12.5
7	Normal Operating Temperature	JPPLM	-20 to 145°C

NA implies "NOT APPLICABLE"

Pack Size : Available in 180 Kgs in MS Barrel