



JUPITER PETROTEC PRODUCTS

[Mfrs of Automotive , Industrial , Speciality Products, Greases & Lube Additives]

Mktg & Admin Office : 18/27, Velu Street, West Mambalam, Chennai-600033

Factory: DP - 109 A, Sidco Industrial Estate, Kakkalur, Thiruvallur District-602003

Email: jupitolubricants@yahoo.co.in / jupitolubricants@gmail.com Website : www.jupitolubricants.com

Phone: 044-24892258 / 24718885 Mobile No. +91 98407 31961 / +91 6374709530

PRODUCT DATA SHEET FOR JUPITOL HEAT TRANS FLUID HTF-36

JUPITOL HEAT TRANS FLUID HTF -36

Product Category	Industrial Speciality
Serial No	019
Date	01.04.2021

Product Description:

Jupitol Heat Transfer Fluid HTF - 36 is product blended with hydro-treated base oil with high oxidation stability. This product is treated with special performance additives to perform as thermic fluid where the bulk temperature may go up to 310°C. The regular operating temperature of the product is 280°C in closed loop circulation. This product has very feeble tendencies of carbon deposit formation. The corrosion resistance property of the oil is extremely good. The low volatility characteristics and low vapour pressure of the oil will help in giving long and stable performance during their service.

Boiling Range From : IBP 350°C – 400 °C

Properties:

- High level of oxidation stability
- Feeble tendency of carbon deposits
- Outstanding corrosion resistance
- Low volatility & Low vapour pressure
- Long and stable performance
- Outstanding sustenance of bulk temperature performance

Typical Characteristics:

S.No.	Test	UOM	Test Method	Specification of Jupitol Heat Trans Fluid - HTF-36
1	Colour	NA	Visual	2.0 to 2.5
2	Clarity	NA	Visual	Clear
3	Density @ 29.5°C	gms/cc	ASTMD-1298	0.870- 0.880
4	Kinematic Viscosity @ 40°C	CSt.	ASTM D-445	34 to 38
5	Flash Point (COC)	°C	ASTM D-92	220 (Min.)
7	Inorganic Acidity	%	ASTM D-1093	Nil
8	Organic Acidity	%	ASTM D-1093	0.05
9	Pour Point	°C	ASTM D-97	-36

Pack Size :- The product is available in pack sizes of 210 Ltrs. Barrel