



JUPITER PETROTEC PRODUCTS

[Mfrs of Automotive , Industrial , Speciality Products, Greases & Lube Additives]

Mktg & Admin Office : 18/27, Velu Street, West Mambalam, Chennai-600033

Factory: DP - 109 A, Sidco Industrial Estate, Kakkalur, Thiruvallur District-602003

Email: jupitolubricants@yahoo.co.in / jupitolubricants@gmail.com Website : www.jupitolubricants.com

Phone: 044-24892258 / 24718885 Mobile No. +91 98407 31961 / +91 6374709530

PRODUCT DATA SHEET

JUPITOL HYDRAULIC OIL AW-150

Product Category	Industrial Lubricants
Serial No	005
Date	01.04.2021

Jupitol Hydraulic Oil (AW Type) -150 is solvent refined high viscosity index mineraloil fortified with anti-wear, anti-oxidation, anti-corrosion and anti-foam additives. It is recommended for circulation systems and other enclosed systems like bearings and gears of general machinery. It is conform to BIS:10522-83 specifications.

Typical Characteristics

S.No	Test	UOM	Test Method	Specification of Jupitol Hydraulic Oil AW -150
1	Appearance (Max.)	NA	Visual	L4.5
2	Clarity	NA	Visual	Clear
3	Density @ 29.5°C	Gms per cc	ASTM D 1298	0.882 (T)
4	Kinematic Viscosity@ 40°C	cSt.	ASTM D 445/IP 71	135 to 165
5	Viscosity Index	NA	ASTM D 2270	+95
6	Cu-Strip Corrosion	-	ASTM D-130	1 Max.
7	Flash Point (COC),Min.	°C	ASTM D 92	230
8	Pour Point	°C	ASTM D 97	-6

NA implies "NOT APPLICABLE".

The values mentioned above are subject to change due to our continuous R & D.

Packs Sold:- The above product is available in 210 Ltrs. Barrel and 20 Ltrs. Mini-drum.