



JUPITER PETROTEC PRODUCTS

[Mfrs of Automotive , Industrial , Speciality Products, Greases & Lube Additives]

Mktg & Admin Office : 18/27, Velu Street, West Mambalam, Chennai-600033

Factory: DP - 109 A, Sidco Industrial Estate, Kakkalur, Thiruvallur District-602003

Email: jupitolubricants@yahoo.co.in / jupitolubricants@gmail.com Website : www.jupitolubricants.com

Phone: 044-24892258 / 24718885 Mobile No. +91 98407 31961 / +91 6374709530

PRODUCT DATA SHEET

JUPITOL HYDRUALIC OIL AW -32

Product Category	Industrial Lubes
Serial No	001
Date	01.04.2021

Product Description:

Jupitol Hydraulic Oil -32 (AW Type) is solvent refined high viscosity index mineral Oil fortified with anti-wear, anti-rust, anti-oxidation, and anti-foam additives. It is recommended for circulation systems and other enclosed systems like bearings and gears of general machinery. It conform to BIS:10522-83 specifications.

Typical Characteristics:

S.No	Test Characteristics	UOM	Test Method	Specifications of Jupitol Hydraulic Oil 32
1	Appearance (Max.)	NA	Visual	L 2.0
2	Clarity	NA	Visual	Clear
3	Density @ 29.5°C	Gms/ cc	ASTM D 1298	0.865 (T)
4	Kinematic Viscosity @ 40°C	cSt.	ASTM D 445/ IP 71	29.8 to 35.2
5	Viscosity Index	NA	ASTM D - 2270	+95 (Min)
6	Cu-Strip Corrosion (Max)	-	ASTM D -130	1
7	Flash Point (COC), Min.	°C	ASTM D - 92	200
8	Pour Point	°C	ASTM D 97	-6
9.	Neutralisation No	mgKOH/ gm	ASTM D-974	1.35(T)

NA implies "NOT APPLICABLE"

The values mentioned above are subject to change due to our continuous R & D

Packs Available: The above product is available in 20 Ltrs Pail & 210 Ltrs. Barrel