



JUPITER PETROTEC PRODUCTS

[Mfrs of Automotive , Industrial , Speciality Products, Greases & Lube Additives]

Mktg & Admin Office : 18/27, Velu Street, West Mambalam, Chennai-600033

Factory: DP - 109 A, Sidco Industrial Estate, Kakkalur, Thiruvallur District-602003

Email: jupitollubricants@yahoo.co.in / jupitollubricants@gmail.com Website : www.jupitollubricants.com

Phone: 044-24892258 / 24718885 Mobile No. +91 98407 31961 / +91 6374709530

PRODUCT DATA SHEET

JUPITOL HYDRAULIC OIL AW -320

Product Category	Industrial Lubricants
Serial No	007
Date	01.04.2021

Product Description

Jupitol Hydraulic Oil -320 (AW Type) is solvent refined high viscosity index mineral oils fortified with anti-wear, anti-oxidation, anti-corrosion and anti-foam additives. It is recommended for circulation systems and other enclosed systems like bearings and gears of general machinery. It conform to BIS:10522-83 specifications.

Typical Characteristics

S.No.	Test	UOM	Test Method	Specification of Jupitol Hydraulic Oil AW - 320
1	Appearance (Max.)	NA	Visual	L5.0
2	Clarity	NA	Visual	Clear
3	Density @ 29.5°C	Gms per cc	ASTM D 1298	0.888 (Typical)
4	Kinematic Viscosity @ 40°C	cSt.	ASTM D 445/IP 71	288 to 352
5	Viscosity Index	NA	ASTM D 2270	+95
6	Cu-Strip Corrosion	-	ASTM D-130	1 Max.
7	Flash Point (COC), Min.	°C	ASTM D 92	240
8	Pour Point	°C	ASTM D 97	-6

NA implies "NOT APPLICABLE".

The values mentioned above are subject to change due to our continuous R & D.

Packs Sold:- The above product is available in 210 Ltrs. Barrel and 20 Ltrs. Mini-drum.