



JUPITER PETROTEC PRODUCTS

[Mfrs of Automotive , Industrial , Speciality Products, Greases & Lube Additives]

Mktg & Admin Office : 18/27, Velu Street, West Mambalam, Chennai-600033

Factory: DP - 109 A, Sidco Industrial Estate, Kakkalur, Thiruvallur District-602003

Email: jupitollubricants@yahoo.co.in / jupitollubricants@gmail.com Website : www.jupitollubricants.com

Phone: 044-24892258 / 24718885 Mobile No. +91 98407 31961 / +91 6374709530

PRODUCT DATA SHEET FOR JUPITOL FLUSHING OIL VG- 12

JUPITOL FLUSHING OIL VG-12

Product Category	Industrial Specialty
Serial No	024
Date	01.04.2021

Product Description:

Jupitol Flushing Oil VG - 12 is paraffinic type high viscosity index mineral oil mildly fortified with special detergent, rust inhibition and anti-oxidant additives to penetrate the flushing surfaces and remove the dust and carbon and deposits etc by simple circulation and also warm circulation at 60 - 80°C

This oil is a non-corrosive and non-hazardous material and does not cause any harm during its use for flushing

This oil shall be used for any type of flushing of machinery housing, pipe lines and other industrial machinery system where mild rusting, carbon settlement and deposits of tiny metal particles and any loosely sticking contaminants need to be removed when manual cleaning is not possible.

Technical Specification:

S. No	Description	Specification
1	Name of Product	Jupitol Flushing Oil VG 12
2	Appearance	Clear Bright Light Yellowish Oil
3	Odour	Mild and Acceptable (Non Offensive)
4	ASTM Colour As per ASTM D 1500	L 1.0
5	Density at 29.5°C gm/cc	0.856 to 0.860
6	Flash Point in °C Min by COC	+ 160°C
7	Kinematic Viscosity at 40°C	11.5 to 14 cSt
8	Viscosity Index	+ 90
9	Pour Point in °C (Max)	6 °C
10	Moisture	Less Than 50 PPM
11	Aniline Point in °C (max)	+ 96 °C
12	Sulphur Content	Less than 0.03%

Pack Size: This product is available in 210 Ltrs MS barrel