



JUPITER PETROTEC PRODUCTS

[Mfrs of Automotive , Industrial , Speciality Products, Greases & Lube Additives]

Mktg & Admin Office : 18/27, Velu Street, West Mambalam, Chennai-600033

Factory: DP - 109 A, Sidco Industrial Estate, Kakkalur, Thiruvallur District-602003

Email: jupitollubricants@yahoo.co.in / jupitollubricants@gmail.com Website : www.jupitollubricants.com

Phone: 044-24892258 / 24718885 Mobile No. +91 98407 31961 / +91 6374709530

PRODUCT DATA SHEET

JUPITOL GENERAL PURPOSE MACHINERY OIL-46	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">Product Category</td><td style="width: 50%;">Industrial Lubricants</td></tr> <tr> <td>Serial No</td><td>020</td></tr> <tr> <td>Date</td><td>01.04.2021</td></tr> </table>	Product Category	Industrial Lubricants	Serial No	020	Date	01.04.2021
Product Category	Industrial Lubricants						
Serial No	020						
Date	01.04.2021						

Product Description

- Jupitol GP Machinery Oil -46 is specially formulated oil to provide tackiness and film strength characteristics. It ensures the adhesion of tough oil film and help in reducing the power consumption, wear and maintenance costs. It has better tackiness and anti-scouring characteristics and is suitable to textile industry applications where they reduce the possibility of cloth staining during different stages of manufacturing. It is conforming to BIS 493:1983 (Amended).
- This oil is general purpose rust and oxidation inhibited type high viscosity oils circulation and general lubrication purpose of industrial equipment bearings, line shafts etc. by hand oiling, bottle oilers or wick feed; and for lubrication of steam engine bearings etc.,

Typical Characteristics

S.No	Description	UOM	Test Method	Specification of Jupitol GPMO 46
1	Appearance (Max.)	NA	Visual	L2.0
2	Clarity	NA	Visual	Clear
3	Density @ 29.5°C	Gms/ cc	ASTM D 1298	0.865 (T)
4	Kinematic Viscosity @ 40°C	cSt.	ASTM D 445/IP 71	41.4 to 50.6
5	Cu-Strip Corrosion	-	ASTM D-130	1 Max.
6	Flash Point (COC), Min.	°C	ASTM D 92	210
7	Pour Point	°C	ASTM D 97	-6

The values mentioned above are subject to change due to our continuous R & D.

Pack Sizes Available: 210 Ltr MS Barrel, 50 Ltr Plastic Carboy & 20 Plastic Pail