



JUPITER PETROTEC PRODUCTS

[Mfrs of Automotive , Industrial , Speciality Products, Greases & Lube Additives]

Mktg & Admin Office : 18/27, Velu Street, West Mambalam, Chennai-600033

Factory: DP - 109 A, Sidco Industrial Estate, Kakkalur, Thiruvallur District-602003

Email: jupitolubricants@yahoo.co.in / jupitolubricants@gmail.com Website : www.jupitolubricants.com

Phone: 044-24892258 / 24718885 Mobile No. +91 98407 31961 / +91 6374709530

PRODUCT DATA SHEET

JUPITOL GENERAL PURPOSE MACHINERY OIL-68	<table> <tr> <td>Product Category</td><td>Industrial Lubricants</td></tr> <tr> <td>Serial No</td><td>021</td></tr> <tr> <td>Date</td><td>01.04.2021</td></tr> </table>	Product Category	Industrial Lubricants	Serial No	021	Date	01.04.2021
Product Category	Industrial Lubricants						
Serial No	021						
Date	01.04.2021						

Product Description

- Jupitol GP Machinery Oil-68 is specially formulated oils to provide tackiness and film strength characteristics. It has ensure the adhesion of tough oil film and help in reducing the power consumption, wear and maintenance costs. It has better tackiness and anti-scouring characteristics and are suitable to textile industry applications where it reduce the possibility of cloth staining during different stages of manufacturing. It conform to BIS 493:1983 (Amended).
- This oil is general purpose rust and oxidation inhibited type high viscosity oils for circulation and general lubrication purpose of industrial equipment bearings, line shafts etc. by hand oiling, bottle oilers or wick feed; and for lubrication of steam engine bearings etc.,

Typical Characteristics

S.No	Description	UOM	Test Method	Specification of Jupitol GPMO 68
1	Appearance (Max.)	NA	Visual	L2.5
2	Clarity	NA	Visual	Clear
3	Density @ 29.5°C	Gms/ cc	ASTM D 1298	0.870 (T)
4	Kin.Viscosity @ 40°C	cSt.	ASTM D 445/IP 71	61.2 to 74.8
5	Cu-Strip Corrosion	-	ASTM D-130	1 Max.
6	Flash Point (COC), Min.	°C	ASTM D 92	210
7	Pour Point	°C	ASTM D 97	-6

The values mentioned above are subject to change due to our continuous R & D.

Pack Sizes Available: 210 Ltr MS Barrel, 50 Ltr Plastic Carbouy & 20 Plastic Pail