



JUPITER PETROTEC PRODUCTS
 [Mfrs of Automotive , Industrial , Speciality Products, Greases & Lube Additives]
 Mktg & Admin Office : 18/27, Velu Street, West Mambalam, Chennai-600033
 Factory: DP - 109 A, Sidco Industrial Estate, Kakkalur, Thiruvallur District-602003
 Email: jupitollubricants@yahoo.co.in / jupitollubricants@gmail.com Website : www.jupitollubricants.com
 Phone: 044-24892258 / 24718885 Mobile No. +91 98407 31961 / +91 6374709530

PRODUCT DATA SHEET

JUPITOL MILL SPIN OIL -22	Product Category	Industrial Lubricants
	Serial No	039
	Date	01.04.2021

Product Description:-

Jupitol Mill Spin Oil -22 is blended from a highly refined low viscosity base stocks possessing excellent oxidation and chemical stability. This oil is additionally fortified with anti-oxidant, anti-wear, anti-rust and defoaming additive.

This oil is recommended for bearing lubrication of high speed textile spindles and machine tool spindles. This oil also find application in timing gears, positive displacement blowers and tracer mechanism and hydraulic systems of precision machine tools.

Applications:-

- Bearing lubrication of high speed textile spindles and machine tool spindles.
- Timing gears, positive displacement blowers and hydraulic systems of precision machine tools.

Typical Characteristics:

S No	Test	UOM	Test Method	Specification of Jupitol Mill Spin Oil -22
1	Colour	NA	ASTM D-1500	L 2.0
2	Clarity	NA	Visual	Clear
3	Density @ 29.5°C	gms/cc	ASTM D-1298	0.865(T)
4	Kinematic Viscosity @ 40°C	CSt.	STM D-445/IP 71	19.5- 24.5
5	Flash Point in °C by (COC), Min.	°C	ASTM D-92	160
6	Copper Corrosion @ 100°C	NA	ASTM D-130	1 (Max.)
7	Pour Point in °C	NA	ASTM D-97/IP-15	-3 (Max.)
8	Rust Test, 24Hrs.	NA	ASTM D-665	Passes

NA implies "NOT APPLICABLE".

The values mentioned above are subject to change due to our continued R & D.

Pack Size :- The product is available in pack sizes of 210 Ltrs. Barrel.